

Order form - rigid foam top-mounted shutter (10/2020)

company \_\_\_\_\_  
 name \_\_\_\_\_  
 street \_\_\_\_\_  
 postcode, city \_\_\_\_\_  
 land \_\_\_\_\_

**reference** \_\_\_\_\_  
**delivery date** \_\_\_\_\_  
 phone: \_\_\_\_\_  
 e-mail: \_\_\_\_\_

**delivery address** (if different)  
 company/Name \_\_\_\_\_  
 street \_\_\_\_\_  
 country \_\_\_\_\_  
 postcode, city \_\_\_\_\_


Request  Order

Measures of units			Box									Guide rails								
pos.	qty.	width	height	guide rail	box size		elongation		adapter profile		reinforce-	static console	box fastenings	box fastening	roller insect sc.	PVC	aluminium	end parts	diagonal cut	notch
		incl. guide rails	incl. box (mind distance to windowsill)	indented	depth	height	min. 60 mm	in mm	universal	other (specify window type)	ment iron (specify window type)									
		mm	mm		265, 305, 365 or spec. size	260	290													
		mm	mm																	
		mm	mm																	
		mm	mm																	
		mm	mm																	

Roller shutter curtain										Operation																
pos.	continuation	Panorama	Pan. Safe	P. Combi ST*	P. Combi RG*	Plus (incl. IS)	Alu-Mini ST	Alu-Mini RG	colour	*with Combi ST or Combi RG		end slat colour or other type	different outlet than standard	motor				radio motor				other controls	cable length 3, 5 or 10 m			
										height	low area of curtain (closed slats)			Becker	Elero	Somfy Hy.	Elero 868	Somfy io	Becker with radio receiv.	wall transm.	hand. transm.					
										mm	mm														m	
										mm	mm															m
										mm	mm															m
										mm	mm															m
										mm	mm															m

**Box version**

inside ac.  outs. ac.



sliding profile (outside ac.) ...  standard (PVC, white) or aluminium in colour \_\_\_\_\_  
 PVC angle outside (white) ....  standard (17 mm) or length (max. 115 mm) \_\_\_\_\_ mm  
 alu. angle outside (white) .. length (max. 65 mm) \_\_\_\_\_ mm  
 alu. end profile outside ....  0 mm  21 mm colour \_\_\_\_\_  
    additional alu. angle outside length (max. 65 mm) \_\_\_\_\_ mm  
 PVC angle inside (in.ac., white) ..  standard (17 mm) or length (max. 115 mm) \_\_\_\_\_ mm  
 alu. angle inside (in.ac.) .. length (max. 65 mm) \_\_\_\_\_ mm colour \_\_\_\_\_

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

place, date \_\_\_\_\_ signature \_\_\_\_\_

e-mail: info@biroll.de fax: +49 (0)8123 989049